

Description of Specification

Non-Interchangeable Type

	MSH	20	LS	2	SS	F0	
Series : MSH							
Size : 20, 30							
Carriage type : Heavy load							
S : Square type							
Ultra heavy load							
LS : Square type							
Number of carriages per rail : 1, 2, 3 ...							
Dust protection option of carriage :							
No symbol, UU, SS, ZZ, DD, KK, LL, RR, HD (refer to Dust Proof [B1-232])							
Preload : FC (Light preload) , F0 (Medium preload) , F1 (Heavy preload)							
Code of special carriage : No symbol, A, B, ...							
Rail type : R (Counter-bore type), T (Tapped hole type)(on the X axis)							
Rail length (mm)(on the X axis)							
Number of rails per axis : No symbol, II, III, IV ... (on the X axis)							
Rail hole pitch from start side (mm, E1)(on the X axis)							
Rail hole pitch to the end side (mm, E2)(on the X axis)							
Rail type : R (Counter-bore type), T (Tapped hole type)(on the Y axis)							
Rail length (mm)(on the Y axis)							
Number of rails per axis : No symbol, II, III, IV ... (on the Y axis)							
Rail hole pitch from start side (mm, E1)(on the Y axis)							
Rail hole pitch to the end side (mm, E2)(on the Y axis)							
Accuracy grade : P							
Code of special rail : No symbol, A, B ...							
Dust protection option of rail : No symbol, /CC, /MC, /MD (refer to Code of Contamination for Rail [B1-233])							

